



APS300 Rental Package 50/60 Hz (Export Only)

FEATURES

EMISSIONS

- EPA Tier 3 and CARB Emissions Certified for non-road mobile applications at all 50 Hz and 60 Hz ratings

CATERPILLAR C9 ATAAC DIESEL ENGINE

- Utilizes ACERT[®] Technology
- Reliable, rugged, durable design
- Field-proven in multiple applications worldwide
- Four-stroke-cycle diesel engine combines durability with minimum weight while providing dependability and economy
- 50/60 Hz Convertibility

CAT SR4B GENERATOR

- Designed to match performance and output characteristics of Caterpillar diesel engines
- Permanent magnet excitation
- Segregated AC, low voltage accessory box provides single point access to accessory connections

ENCLOSURE

- Made with 12-gauge steel
- Single point lifting eye
- Sound attenuated
- Convenient hand holds and steps for safe operation
- Two coat polyester powder-coated finish

ENVIROMENTALLY FRIENDLY DESIGN

- Sound attenuated for low noise operation
- OSHA compliant safe design
- 110% spill containment for coolant and oil
- UL 142 certified dual wall fuel tank

MULTI-VOLTAGE DISTRIBUTION PANEL

- High/low wye, manual changeover board
- Load door safety switch
- Rust-free hinges on rear opening door
- Adequate space for line and plug connection without interference
- Remote start and stop contacts
- Single main breaker with adjustable trip

SINGLE-SOURCE SUPPLIER

- Complete systems designed at Altorfer Power Systems

PRODUCT SUPPORT

- Parts availability through the Caterpillar dealer network and direct through Altorfer Power Systems
- 99.7% of parts orders filled within 48 hours.
- Caterpillar dealer service technicians are trained to service every aspect of your electric power generation system.

FACTORY INSTALLED STANDARD EQUIPMENT

Air Inlet System	Air cleaner, dual element Turbocharger
Charging System	Battery charger Heavy duty charging alternator
Control Panel	Generator controls and monitoring Fuel tank monitoring Engine controls and monitoring Digital displays
Cooling System	Fan and belt guards Base mounted radiator Air to air after cooling
Distribution Panel	Lockable doors Load door safety switch (trips breaker upon door opening). Individual bus bar connections Circuit breaker with 24 VDC shunt trip Remote start/stop contacts Shore power connections Manual change over board Convenience receptacle package
Enclosure	Sound attenuated 12-gauge steel Lockable doors Separate vented battery compartment Single point lifting Exterior oil and water drains with interior valves. Hidden exterior fuel drain Hand holds and steps Powder-coated finish
Fuel System	Primary fuel filter/water separator UL 142 dual wall fuel tank, 1667 L (440 g) Radiator-mounted fuel cooler
Generator	Brushless, permanent magnet Coastal corrosion protection Shock mounted VR6 voltage regulator Space heater UL approved Reconnectable 12 lead
Mounting System	Generator soft mounted to base Base contains integral fuel tank Skiddable structural steel design 110% oil and coolant spill containment
Starting System	Electric starting motor Battery set with disconnect switch Jacket water heater with thermostat, shut-off valves



SPECIFICATIONS

CAT SR4B GENERATOR

Frame size. 449
Type permanent magnet brushless
Construction single bearing, close coupled
Three phase 12 lead reconnectable
Insulation Class H with Coastal insulation protection
IP rating 22
Alignment Pilot shaft
Voltage regulator . 3-phase sensing with Volts-per-Hertz
Voltage regulation ± ½% steady state/± ½%
No load to full load
TIF Less than 50
THD Less than 5%

CAT ENGINE

C9 ATAAC, 4-stroke-cycle water-cooled diesel
Bore – mm (in)112 (4.41)
Stroke –mm (in)149 (5.87)
Displacement – L (cu in)8.8 (537)
Compression ratio16.1:1
AspirationTurbocharged- ATAAC
Engine control ADEM™ A4

CONTROL PANEL – CAT EMCP 4.2

24 Volt DC Control
NEMA 1, IP22 enclosure
Lockable hinged door
Enclosure mounted
Single location customer connector point
16 light alarm module with alarm horn
Electric fuel level gauge

DISTRIBUTION PANEL

Wiring Descriptions

- 1. 1200A main breaker with adjustable trip and 24V DC shunt trip
- 2. High/low wye manual change over board
- 3. 50 amp 240V branch breaker
- 4. 20 amp 240V branch breaker
- 5. 20 amp 120V branch breaker
- 6. 15 amp 120V branch breaker
- 7. 50 amp 120/240V twistlock receptacle
- 8. 20 amp 240V twistlock receptacle
- 9. 20 amp 120V twistlock receptacle (2x)
- 10. 20 amp 120V ground fault interrupter, (2x)
- 11. 15 amp 120V ground fault interrupter, duplex receptacle (2x)
- 12. 30 amp 120V battery charger/generator space heater shore power receptacle
- 13. 30 amp 120V JWH shore power receptacle
- 14. Remote start/stop contacts
- 15. 12.7 mm (1/2") ground stud
- 16. Load connection bus board
- 17. [6.35 mm x 101.6 mm (1/4" x 4") bus bars]

Overall Dimensions



	Package	
Length	4597.4 mm	181 in
Width	1498.6 mm	59 in
Height	2387.6 mm	94 in

TECHNICAL DATA

Power Rating		<u>Stand by</u>	<u>TMI Ref.</u>	<u>Prime</u>	<u>TMI Ref.</u>
60 Hz	ekW	300	DM8168	275	DM8500
50 Hz	kVA		310		DM8503
Shipping Weight (Dry)	kg (lb)	4980 (10,980)			
Maximum Fuel Capacity Weight	kg (lb)	6278 (13,840)			
Engine Lubricating Oil Capacity	L (qts)	40 (42.3)			
Engine Coolant Capacity with Radiator	L (gal)	36 (9.5)			
Fuel Tank Capacity	L (gal)	1516 (400)			
Fuel Consumption	L/hr (gal/hr)	89.1 (23.5)		81.3 (21.5)	
Fuel Consumption (75% Prime)	L/hr (gal/hr)	63.5 (16.8)			
Running Time @ 75% Prime	Hours	24			
Sound Level					
Standby	dB(A)	74.72			
No load @ 7 m (23 ft)	dB(A)	70.20			
Prime	dB(A)	73.49			
Ambient Capability	Deg C (Deg F)	43 (109.4)			

Rating Definitions and Conditions

Meets or Exceeds International Specifications:
 NEMA MG1-32, IEC 60034, CSA, 98/37/EEC, 72/23/EEC, UL 508, UL142, ISO3046/1, ISO8528, 89/336/EEC

Standby- Output available with varying load for the duration of the interruption of the normal source power. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046/1, AS2789, DIN6271, BS5514.

Prime- Output available with varying load for an unlimited time. Prime power in accordance with ISO8528. 10% overload power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514 available on request.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046/1, DIN6271 and BS5514 standard conditions.

ALTORFER
Power Systems



Fuel rates are based on fuel oil of 35° API [@ 16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lb/U.S. gal).

Additional ratings may be available for specific customer requirements. Consult your Altorfer representative for details.